



Horti-Sky

HL09-150

TECHNICAL DATASHEET

2023



Product features


Housing material	Aluminum
Optics materials	Conformal coating (transmission >97%)
Radiation angle	120°
Protection degree	IP65 (dust and watertight)

Technical data

Power consumption	150W
System efficacy (±10%)	2.45 μmol/J @230Vac
PAR Output	368 μmol/s
ePAR Output	378 μmol/s
Voltage input	100-277Vac,50-60Hz
Current Range	1.5A @ 100V , 0.54A @ 277V
Isolation Class	Class I
Heat BTU Generated	511.5 BTU
Power Factor	> 0.9
Dimming	0-10V

* The tolerance for power is ±5%

Drawing




Dimensions	1148 x 72 x 60.4mm 45.2" x 2.84" x 2.38"
Net Weight	2.1kg/5.1 lbs
Qty/CTN	1 pc
Gross Weight	3kg / 6.6 lbs
CTN SIZE	1195 x 130 x 120mm 47.5" x 5.1" x 4.7"
Operation conditions	0°C to 40°C / 32°F to 104°F (95% RH)
Storage conditions	-40°C to 70°C / -40°F to 158°F (85% RH)
Warranty	5 years


* The tolerance for weight is ±6%

Spectrum Chart

HL09-P01-B02



Accessories




or



Standard: 2*V cords attach to 2*rope ratchet

Optional: Ceiling mounting bracket * 2 pcs

IES Test



Compliance

- CE
- ETL
- Low Voltage Directive (LVD)
- Electromagnetic Compatibility Directive (EMC)
- Restriction of Hazardous Substances (RoHS) Directive

Technical Datasheet Designed and produced in the Atop Lighting. © 2023, Atop. All rights reserved.

Atop Lighting

Building A, Jian'an Road No.3,
Tang Wei Community, Fu Yong Street,
Bao An Distric, Shen Zhen, China.

T +8675523573307
E info@atophort.com
W www.atophort.com

