



Horti-Sky

HL09-150

TECHNICAL DATASHEET

2023



Product features


Housing material	Aluminum
Optics materials	Conformal coating (transmission >97%)
Radiation angle	120°
Protection degree	IP65 (dust and watertight)

Technical data

Power consumption	150W
System efficacy (±10%)	2.46 μmol/J @230Vac
PAR Output	369 μmol/s
ePAR Output	377 μmol/s
Voltage input	100-277Vac,50-60Hz
Current Range	1.5A @ 100V , 0.54A @ 277V
Isolation Class	Class I
Heat BTU Generated	511.5 BTU
Power Factor	> 0.9
Dimming	0-10V

* The tolerance for power is ±5%

Drawing




Dimensions	1148 x 72 x 60.4mm 45.2" x 2.84" x 2.38"
Net Weight	2.1kg/5.1 lbs
Qty/CTN	1 pc
Gross Weight	3kg / 6.6 lbs
CTN SIZE	1195 x 130 x 120mm 47.5" x 5.1" x 4.7"
Operation conditions	0°C to 40°C / 32°F to 104°F (95% RH)
Storage conditions	-40°C to 70°C / -40°F to 158°F (85% RH)
Warranty	5 years


* The tolerance for weight is ±6%

Spectrum Chart

HL09-P02-B09



IES Test



Technical Datasheet Designed and produced in the Atop Lighting. © 2023, Atop. All rights reserved.

Accessories



Standard: 2*V cords attach to 2*rope ratchet

or



Optional: Ceiling mounting bracket * 2 pcs

Compliance

CE
ETL
Low Voltage Directive (LVD)
Electromagnetic Compatibility Directive (EMC)
Restriction of Hazardous Substances (RoHS) Directive

Atop Lighting

Building A, Jian'an Road No.3,
Tang Wei Community, Fu Yong Street,
Bao An Distric, Shen Zhen, China.

T +8675523573307
E info@atophort.com
W www.atophort.com

